

color+

Description		
Multi-layer floors (Multi-Layer-Flooring) according to EN 13329 for glueless installation		
Fields of use		
The Multi-layer floor color+ is suitable for heavy domestic and heavy commercial use (EN 13329 - 33). "Allgemeine bauaufsichtliche Zulassung" Nr. Z-156.606-709		
Technical details		
<b>Dimensions (Decor)</b>	1488 x 293 mm	
<b>Thickness of element</b>	11,4 mm	
<b>Package</b>	Pack: 4 elements / 1,74 m <sup>2</sup> / 20 kg Pallet: 45 packs / 78,30 m <sup>2</sup> / 915 kg	
<b>Quality Guarantee*</b>	lifetime	
Domestic area	10 years	
Commercial area		
Design		
	1	<b>Layer (1-3)</b> 1 mm HPL - X-Protect-Surface <b>Surface</b> - high gloss
	2	<b>Decor paper</b>
	3	<b>underlay sheets</b>
	4	<b>coreboard</b> Aqua-Protect®
	5	<b>Backing 1 mm HPL</b>
	6	<b>Click system (glueless)</b> LocTec click joint
Classification		
	<b>Test Method Standard</b>	<b>Marking acc. Standard</b>
<b>Level of use 23</b> Heavy domestic use	EN 685	Corridors, living rooms, kitchens, home offices
<b>Level of use 33</b> Heavy commercial use	EN 685	Large offices, public buildings, department stores
<b>LocTec</b>	-	Optimum fit with longer durability
<b>Aqua Protect</b>	-	Especially protected coreboard against moisture
<b>Suitable for cleaning with Kärcher Floor scrubber BR 400</b>	-	-
<b>Scrub resistance</b>	Martindale	highly scrub resistant
<b>AC5</b>	EN 13329, annex E	AC 5
<b>Impact resistance</b>	EN 13329, annex F	IC 3
<b>Reaction to fire</b>	EN 13501-1	B <sub>fl</sub> - s1
<b>Dynamic coefficient of friction</b>	EN 13893 EN 14041	μ ≥ 0.3 DS
<b>Resistance to staining</b>	EN 438-2	Materials of group 1 + 2: ≥ grade 5 Materials of group 3: ≥ grade 4
<b>Resistance to cigarette burns</b>	EN 438-2	≥ Grad 4 resistant (no damage of the surface)
<b>Light fastness</b>	EN 438-2	Grey scale: ≥ 4
<b>Static indentation</b>	EN 433	No visible change, 0,00 mm indentation
<b>Effect of a furniture leg</b>	EN 424	No visible damage, when tested with foot type 0
<b>Effect of a castor chair</b>	EN 425	No change in appearance or damage, as defined in EN 425. Single-wheel castors, as defined in EN 12529:1998, 5.4.4.2 (Type W) shall be used.
<b>Thermal resistance</b> Underfloor heating - suitable in connection with underlay material and PE-foil as moisture barrier	DIN EN 12664	< 0,08 (m <sup>2</sup> K)/W - floating installation
<b>E1</b>	EN 717-2	E1
<b>Environment/Disposal</b>	<u>Private disposal:</u> like laminated furniture; possible with normal domestic refuse <u>Commercial disposal:</u>	Refuse-key-no. AVV 170201

\* acc. to the Witex guarantee provisions  
\*\* acc. to the Witex implementation provisions

Relevant Information:  
- Cleaning and care: see separate cleaning & care instruction  
- No release for glue-down  
- Technical subjects can be changed by Witex