

design clic multiline flooring

Description			
Pre-finished parquet produced under precondition EN 13489 - glueless installation with LocTec Wood			
Fields of use			
Pre-finished parquet design clic is suitable for all domestic area			
Technical details		Design	
Dimensions (Decor)	2280 x 204 mm		1 Wood layer Real wood (approx. 4,3 mm) Wood specifications/grades <i>classic</i> : beech, oak Description classic grade - relatively high evenness of the wood structure - low knot or brown heartwood or splint content - natural colour variation in the wood
Thickness of element	15 mm		2 Middle Core High-quality pine rifts (softwood) and plywood support at the narrow side
Package	Carton: 6 elements / 2,79 m ² / 21 kg Pallet: 45 cartons / 125,60 m ² / 945 kg		3 Countermove Softwood
Quality Guarantee**	Domestic area: 25 years		4 Lacquering UV-Scratch-Protect 6 layers lacquered with matt-finish
			5 Locking system (glueless) LocTec Wood
Classification			
		Test Method Standard	Marking acc. Standard
	Length side Uniclic-system Narrow side Snap-System	-	Automatically aligning at the long side of the element. Perfect fit with longer durability of the end joint connection
	UV-Scratch-Protect lacquering	-	-
	Level of use C Especially heavy use	ÖNORM C 2354	Restaurants, salesrooms, premises for the public area
	Reaction to fire	EN 13501-1	C _{fl} - s1 (correspond with B1)
	Effect of a castor chair	EN 425	No visible change Chair wheels type W - use a protection mat in the immediate area of the chair wheels - use felt pads under tables and chairs
	Thermal resistance Underfloor heating - suitable up to max. 26 °C surface temperature in connection with PE-foil for moisture barrier	EN 12664	0,10 m ² k/W - floating installation (in test)
	Formaldehyde emission	EN 14041	E1
	PEFC - Pan European Forest Certification certified minimum 70 % of the used wood	EN 45011	Certified from HolzCert Austria
	Environment/Disposal like laminated furniture / possible with normal domestic refuse / at commercial heating disposal plant	-	-

Relevant information:

- Cleaning and care: see separate cleaning & care instruction.
- design clic can also be installed completely glued to the subfloor. Please check details with our technical department.
- Technical subjects can be changed by Witex.

*) acc. to Witex quality guarantee description