

# elastoclic design vinyl - wood

Description																																																																																					
Long-lasting multi-layer floor (Multi-Layer-Flooring) according to EN 14085 for glueless installation																																																																																					
Fields of use																																																																																					
elastoclic design vinyl is suitable for heavy domestic and moderate commercial use (class 23, 31 EN 649). *Allgemeine bauaufsichtliche Zulassung*: Nr. Z-156.610-710																																																																																					
Technical details	Design																																																																																				
<table border="1"> <tr> <td><b>Dimensions (Decor)</b></td> <td>1194 x 212 mm</td> </tr> <tr> <td><b>Thickness of element</b></td> <td>10,0 mm (incl. Sound-Protect)</td> </tr> <tr> <td><b>Package</b></td> <td>Pack: 7 elements / 1,77 m<sup>2</sup> / 19,22 kg Pallet: 53 packs / 92,04 m<sup>2</sup> / 1014,6 kg</td> </tr> <tr> <td><b>Quality Guarantee*</b></td> <td>Domestic area: 15 years / lifetime Commercial area: 5 years</td> </tr> </table>	<b>Dimensions (Decor)</b>	1194 x 212 mm	<b>Thickness of element</b>	10,0 mm (incl. Sound-Protect)	<b>Package</b>	Pack: 7 elements / 1,77 m <sup>2</sup> / 19,22 kg Pallet: 53 packs / 92,04 m <sup>2</sup> / 1014,6 kg	<b>Quality Guarantee*</b>	Domestic area: 15 years / lifetime Commercial area: 5 years																																																																													
<b>Dimensions (Decor)</b>	1194 x 212 mm																																																																																				
<b>Thickness of element</b>	10,0 mm (incl. Sound-Protect)																																																																																				
<b>Package</b>	Pack: 7 elements / 1,77 m <sup>2</sup> / 19,22 kg Pallet: 53 packs / 92,04 m <sup>2</sup> / 1014,6 kg																																																																																				
<b>Quality Guarantee*</b>	Domestic area: 15 years / lifetime Commercial area: 5 years																																																																																				
<table border="1"> <thead> <tr> <th colspan="2">Classification</th> <th>Test Method Standard</th> <th>Marking acc. Standard</th> </tr> </thead> <tbody> <tr> <td></td> <td><b>Level of use 23</b> Heavy domestic use</td> <td>EN 649</td> <td>Living rooms, dining rooms, kitchens, entrance halls, corridors</td> </tr> <tr> <td></td> <td><b>Level of use 31</b> Moderate commercial use</td> <td>EN 649</td> <td>Hotel rooms, small offices</td> </tr> <tr> <td></td> <td><b>Class 32*</b> General commercial use</td> <td colspan="2">Proactive long-term protection Suitable for use in more demanding commercial sectors by applying / adding Dr. Schutz's PU Sealer Systems - (separate Witex maintenance instructions required).</td> </tr> <tr> <td></td> <td>LocTec clic system</td> <td>-</td> <td>Optimum fit with longer durability</td> </tr> <tr> <td></td> <td>HDF-Protect®</td> <td>-</td> <td>Protection against swelling</td> </tr> <tr> <td></td> <td>Suitable for cleaning with Kärcher Floor scrubber BR 400</td> <td>-</td> <td>-</td> </tr> <tr> <td></td> <td>Classification of group of wear reaction</td> <td>DIN EN 649</td> <td>Class T</td> </tr> <tr> <td></td> <td>Impact sound reduction <sup>5</sup></td> <td>DIN EN ISO 140-8</td> <td>~ 21 dB</td> </tr> <tr> <td></td> <td>Determination of resistance to staining</td> <td>EN 423 / DIN 51958</td> <td>Class 0 - good</td> </tr> <tr> <td></td> <td>Light fastness</td> <td>EN ISO 105-B02</td> <td>≥ 6 blue wool scale</td> </tr> <tr> <td></td> <td>Static indentation</td> <td>EN 433</td> <td>0,023 mm indentation</td> </tr> <tr> <td></td> <td>Effect of a furniture leg</td> <td>EN 424</td> <td>No visible damage, when tested with foot type 0</td> </tr> <tr> <td></td> <td>Formaldehyde emission</td> <td>DIN EN 14041</td> <td>E 1</td> </tr> <tr> <td></td> <td>Reaction to fire</td> <td>EN 13501-1</td> <td>B<sub>fl</sub> - s1</td> </tr> <tr> <td></td> <td>Slip resistance (oil)</td> <td>DIN 51130: 2004 - 06</td> <td>R 10</td> </tr> <tr> <td></td> <td>Dynamic coefficient of friction</td> <td>EN 13893 EN 14041</td> <td>μ ≥ 0.30 DS</td> </tr> <tr> <td></td> <td>Effect of a castor chair</td> <td>EN 425</td> <td>No change in appearance or damage, as defined in EN 425. Single-wheel castors, as defined in EN 12529:1998, 5.4.4.2 (Type W) shall be used.</td> </tr> <tr> <td></td> <td>Anti-Static characteristics</td> <td>DIN EN 1815</td> <td>Anti-static (overlay)</td> </tr> <tr> <td></td> <td><b>Thermal resistance</b> Underfloor heating - suitable in connection with PE-foil as moisture barrier</td> <td>EN 12667 EN 14041</td> <td>0,06 (m<sup>2</sup>K) / W - floating installation</td> </tr> <tr> <td colspan="2"><b>Environment/Disposal</b></td> <td>Private disposal: like laminated furniture; possible with normal domestic refuse Commercial disposal:</td> <td>Refuse-key-no. AVV 200138</td> </tr> </tbody> </table>		Classification		Test Method Standard	Marking acc. Standard		<b>Level of use 23</b> Heavy domestic use	EN 649	Living rooms, dining rooms, kitchens, entrance halls, corridors		<b>Level of use 31</b> Moderate commercial use	EN 649	Hotel rooms, small offices		<b>Class 32*</b> General commercial use	Proactive long-term protection Suitable for use in more demanding commercial sectors by applying / adding Dr. Schutz's PU Sealer Systems - (separate Witex maintenance instructions required).			LocTec clic system	-	Optimum fit with longer durability		HDF-Protect®	-	Protection against swelling		Suitable for cleaning with Kärcher Floor scrubber BR 400	-	-		Classification of group of wear reaction	DIN EN 649	Class T		Impact sound reduction <sup>5</sup>	DIN EN ISO 140-8	~ 21 dB		Determination of resistance to staining	EN 423 / DIN 51958	Class 0 - good		Light fastness	EN ISO 105-B02	≥ 6 blue wool scale		Static indentation	EN 433	0,023 mm indentation		Effect of a furniture leg	EN 424	No visible damage, when tested with foot type 0		Formaldehyde emission	DIN EN 14041	E 1		Reaction to fire	EN 13501-1	B <sub>fl</sub> - s1		Slip resistance (oil)	DIN 51130: 2004 - 06	R 10		Dynamic coefficient of friction	EN 13893 EN 14041	μ ≥ 0.30 DS		Effect of a castor chair	EN 425	No change in appearance or damage, as defined in EN 425. Single-wheel castors, as defined in EN 12529:1998, 5.4.4.2 (Type W) shall be used.		Anti-Static characteristics	DIN EN 1815	Anti-static (overlay)		<b>Thermal resistance</b> Underfloor heating - suitable in connection with PE-foil as moisture barrier	EN 12667 EN 14041	0,06 (m <sup>2</sup> K) / W - floating installation	<b>Environment/Disposal</b>		Private disposal: like laminated furniture; possible with normal domestic refuse Commercial disposal:	Refuse-key-no. AVV 200138
Classification		Test Method Standard	Marking acc. Standard																																																																																		
	<b>Level of use 23</b> Heavy domestic use	EN 649	Living rooms, dining rooms, kitchens, entrance halls, corridors																																																																																		
	<b>Level of use 31</b> Moderate commercial use	EN 649	Hotel rooms, small offices																																																																																		
	<b>Class 32*</b> General commercial use	Proactive long-term protection Suitable for use in more demanding commercial sectors by applying / adding Dr. Schutz's PU Sealer Systems - (separate Witex maintenance instructions required).																																																																																			
	LocTec clic system	-	Optimum fit with longer durability																																																																																		
	HDF-Protect®	-	Protection against swelling																																																																																		
	Suitable for cleaning with Kärcher Floor scrubber BR 400	-	-																																																																																		
	Classification of group of wear reaction	DIN EN 649	Class T																																																																																		
	Impact sound reduction <sup>5</sup>	DIN EN ISO 140-8	~ 21 dB																																																																																		
	Determination of resistance to staining	EN 423 / DIN 51958	Class 0 - good																																																																																		
	Light fastness	EN ISO 105-B02	≥ 6 blue wool scale																																																																																		
	Static indentation	EN 433	0,023 mm indentation																																																																																		
	Effect of a furniture leg	EN 424	No visible damage, when tested with foot type 0																																																																																		
	Formaldehyde emission	DIN EN 14041	E 1																																																																																		
	Reaction to fire	EN 13501-1	B <sub>fl</sub> - s1																																																																																		
	Slip resistance (oil)	DIN 51130: 2004 - 06	R 10																																																																																		
	Dynamic coefficient of friction	EN 13893 EN 14041	μ ≥ 0.30 DS																																																																																		
	Effect of a castor chair	EN 425	No change in appearance or damage, as defined in EN 425. Single-wheel castors, as defined in EN 12529:1998, 5.4.4.2 (Type W) shall be used.																																																																																		
	Anti-Static characteristics	DIN EN 1815	Anti-static (overlay)																																																																																		
	<b>Thermal resistance</b> Underfloor heating - suitable in connection with PE-foil as moisture barrier	EN 12667 EN 14041	0,06 (m <sup>2</sup> K) / W - floating installation																																																																																		
<b>Environment/Disposal</b>		Private disposal: like laminated furniture; possible with normal domestic refuse Commercial disposal:	Refuse-key-no. AVV 200138																																																																																		
* acc. to the Witex guarantee provisions		<b>Relevant Information:</b> - Cleaning and care: see separate cleaning & care instruction - Technical subjects can be changed by Witex																																																																																			