

elastoclic pur

Description			
Long-lasting PUR - floor covering element for glueless installation			
Fields of use			
elastoclic pur is suitable for heavy domestic use and very heavy commercial use (class 23, 34 EN 1817) "Allgemeine bauaufsichtliche Zulassung": Z-156.610-427			
Technical details		Design	
Dimensions (Decor)			1
Panel Square	1176 x 294 mm 294 x 294 mm		2
Thickness of element	12 mm (incl. Sound-Protect)		3
Package (Panel)	Carton: 5 elements / 1,73 m ² / 22 kg Pallet: 45 cartons / 77,85 m ² / 970 kg		4
Package (Square)	Carton: 5 squares / 0,43 m ² / 5,3 kg Pallet: 135 cartons / 58,05 m ² / 720 kg		
Quality Guarantee*	Domestic area: 15 years Commercial area: 5 years		
		"Allgemeine bauaufsichtliche Zulassung" (meets the requirements)	

Classification			
		Test Method Standard	Marking acc. Standard
	Level of use 23 Heavy domestic use	EN 1817	Living rooms, dining rooms, kitchens, entrance halls, corridors
	Level of use 34 Very heavy commercial use	EN 1817	Lobby's, open plan offices, counter, department stores
	LocTec clic system	-	Optimum fit with longer durability
	Aqua-Protect® core board	-	Protection against swelling (suitable for kitchens and bathrooms)
	Suitable for machine	WT method	Suitable for Kärcher Floor scrubber BR 400
	Antimicrobial	-	No culture medium for bacteria and fungi
	Classification of group of wear reaction	DIN EN 649	Class T
	Determination of resistance to staining	EN 423	Limited resistant
	Resistance to cigarette burns	EN 438-2	Resistant (no damaging of the surface)
	Light fastness	EN ISO 105-B02	≥ 6 blue wool scale
	Static indentation	EN 433	No visible change, i.e. ≤ 0,01 mm indentation using a straight steel cylinder, Ø = 11,30 mm.
	Sound design	EPLF standard 021029-3	Standard is not yet approved
	Formaldehyde emission	DIN EN 14041	E1
	Reaction to fire	DIN 4102 T1 EN 13501-1	B1 C _{fl} s1 (in test)
	Dynamic coefficient of friction, formerly slip resistance	EN 13893 EN 14041 replace the former standard ZH 1/571	μ ≥ 0.3 DS replace the former characteristic R9
	Effect of a castor chair	EN 425	No change in appearance or damage, as defined in EN 425. Single-wheel castors, as defined in EN 12529:1998, 5.4.4.2 (Type W) shall be used.
	Anti-Static characteristics	DIN EN 1815	Antistatic (overlay)
	Thermal resistance Underfloor heating - suitable in connection with PE-foil as moisture barrier	DIN EN 12664	≤ 0,15 m ² k/w - floating installation
	Environment/Disposal possible with normal domestic refuse	-	-

Relevant information
- Please note the installation of one charge in one room - Cleaning and care: see separate cleaning & care instruction - Technical subjects can be changed by Witex

*) acc. to Witex quality guarantee description