

# euro actual plus

Description		
Direct Pressure Laminate according to EN 13329 for glueless installation		
Fields of use		
Laminate euro actual plus is suitable for heavy domestic and general commercial use (EN 13329 - 32) "Allgemeine bauaufsichtliche Zulassung": Z-156.606-410		
Technical details		
<b>Dimensions (Decor)</b>	1280 x 192 mm	
<b>Thickness of element</b>	10 mm	
<b>Package</b>	Pack: 7 elements / 1,72 m <sup>2</sup> / 16 kg Pallet: 52 packs / 89,44 m <sup>2</sup> / 847 kg	
<b>Quality Guarantee*</b> Domestic area Commercial area	20 years / lifetime 5 years	
Design		
	<b>1</b>	<b>Overlay</b> Especially resistant melamine resin overlay  <b>Surface (depend on decor)</b> - fine wooden pore - textured wooden pore - matt surface - handscraped I
	<b>2</b>	<b>Decor paper</b> Decorative film
	<b>3</b>	<b>Coreboard</b> HDF
	<b>4</b>	<b>Edge sealing</b> Protection against moisture
	<b>5</b>	<b>Click system (glueless)</b> LocTec Click joint
	<b>6</b>	<b>Laminated underlay</b> Sound-Protect Eco Plus acoustic system
Classification		
	<b>Test Method Standard</b>	<b>Marking acc. Standard</b>
<b>Level of use 23</b> Heavy domestic use	EN 13329	Corridors, living rooms, kitchens, home offices
<b>Level of use 32</b> General commercial use	EN 13329	Offices, boutiques, cafés
<b>LocTec</b>	-	Optimum fit with longer durability
<b>HDF</b>	-	HDF board
<b>AC4</b>	EN 13329, annex E	AC 4
<b>Impact resistance</b>	EN 13329, annex F	IC 2
<b>Reaction to fire</b>	DIN 4102 T1 EN 13501-1	B1 C <sub>fl</sub> s1
<b>Dynamic coefficient of friction</b>	EN 13893 EN 14041	μ ≥ 0.3 DS
<b>Resistance to staining</b>	EN 438-2	Materials of group 1 + 2: ≥ grade 5 Materials of group 3: ≥ grade 4
<b>Resistance to cigarette burns</b>	EN 438-2	Slight change of the surface ≥ grade 4
<b>Light fastness</b>	EN ISO 105 - B02 EN 20105 - A02	Blue wool scale: ≥ 6 Grey scale: ≥ 4
<b>Static indentation</b>	EN 433	No visible change, i.e. ≤ 0,01 mm indentation using a straight steel cylinder, Ø = 11,30 mm.
<b>Effect of a furniture leg</b>	EN 424	No visible damage, when tested with foot type 0
<b>Effect of a castor chair</b>	EN 425	No change in appearance or damage, as defined in EN 425. Single-wheel castors, as defined in EN 12529:1998, 5.4.4.2 (Type W) shall be used.
<b>Thermal resistance</b> Underfloor heating - suitable in connection with underlay material and PE-foil as moisture barrier	DIN EN 12664	< 0,07 (m <sup>2</sup> K)/W - floating installation
<b>E1</b>	DIN EN 14041	E1
<b>Environment/Disposal</b>	<u>Private disposal:</u> like laminated furniture; possible with normal domestic refuse <u>Commercial disposal:</u>	Refuse-key-no. AVV 170201
* acc. to the Witex guarantee provisions ** acc. to the Witex implementation provisions		<b>Relevant Information:</b> - Cleaning and care: see separate cleaning & care instruction - Technical subjects can be changed by Witex