

piazza

Description															
Direct Pressure Laminate according to EN 13329 for glueless installation															
Fields of use															
Laminate piazza is suitable for heavy domestic and heavy commercial use (EN 13329 - 33) "Allgemeine bauaufsichtliche Zulassung": Z-156.606-410															
Technical details		Design													
Dimensions (Decor)	1280 x 192 mm		<table border="1"> <tr> <td>1</td> <td>Overlay Especially resistant melamine resin overlay</td> </tr> <tr> <td>2</td> <td>Decor paper Decorative film</td> </tr> <tr> <td>3</td> <td>Underlay Additional strong film</td> </tr> <tr> <td>4</td> <td>Coreboard Aqua-Protect® FSC certified</td> </tr> <tr> <td>5</td> <td>Edge sealing Protection against moisture</td> </tr> <tr> <td>6</td> <td>Click system (glueless) LocTec click joint</td> </tr> </table>	1	Overlay Especially resistant melamine resin overlay	2	Decor paper Decorative film	3	Underlay Additional strong film	4	Coreboard Aqua-Protect® FSC certified	5	Edge sealing Protection against moisture	6	Click system (glueless) LocTec click joint
1	Overlay Especially resistant melamine resin overlay														
2	Decor paper Decorative film														
3	Underlay Additional strong film														
4	Coreboard Aqua-Protect® FSC certified														
5	Edge sealing Protection against moisture														
6	Click system (glueless) LocTec click joint														
Thickness of element	8 mm														
Package	Pack: 9 elements / 2,21 m ² / 17,7 kg Pallet: 52 packs / 114,92 m ² / 935,4 kg														
Quality Guarantee* Domestic area Commercial area	lifetime 10 years														
Classification															
		Test Method Standard	Marking acc. Standard												
	Level of use 23 Heavy domestic use	EN 13329	Corridors, living rooms, kitchens, home offices												
	Level of use 33 Heavy commercial use	EN 13329	Large offices, public buildings, department stores												
	LocTec click system	-	Optimum fit with longer durability												
	Aqua-Protect® coreboard	-	Especially protected coreboard against moisture												
	Suitable for cleaning with Kärcher Steam-Cleaner DE 4002 and Kärcher Floor scrubber BR 400	-	-												
	Abrasion resistance	EN 13329, annex E	AC 5												
	Impact resistance	EN 13329, annex F	IC 3												
	Reaction to fire	DIN 4102 T1 EN 13501-1	B1 C _{fl} s1												
	Dynamic coefficient of friction	EN 13893 EN 14041	μ ≥ 0.3 DS												
	Anti-Static characteristics	Test of Witex according to DIN EN 1815	Witex laboratory test is fulfilled												
	Resistance to staining	EN 438-2	Materials of group 1 + 2: ≥ grade 5 Materials of group 3: ≥ grade 4												
	Resistance to cigarette burns	EN 438-2	Slight change of the surface ≥ grade 4												
	Light fastness	EN ISO 105 - B02 EN 20105 - A02	Blue wool scale: ≥ 6 Grey scale: ≥ 4												
	Static indentation	EN 433	No visible change, i.e. ≤ 0,01 mm indentation using a straight steel cylinder, Ø = 11,30 mm.												
	Effect of a furniture leg	EN 424	No visible damage, when tested with foot type 0												
	Effect of a castor chair	EN 425	No change in appearance or damage, as defined in EN 425. Single-wheel castors, as defined in EN 12529:1998, 5.4.4.2 (Type W) shall be used.												
	Thermal resistance Underfloor heating - suitable in connection with underlay material and PE-foil as moisture barrier	DIN EN 12664	< 0,06 (m ² K)/W - floating installation												
	Formaldehyde emission	DIN EN 14041	E1												
Environment/Disposal		<u>Private disposal:</u> like laminated furniture; possible with normal domestic refuse <u>Commercial disposal:</u>	Refuse-key-no. AVV 170201												

* acc. to the Witex guarantee provisions
** acc. to the Witex implementation provisions

Relevant Information:
- Cleaning and care: see separate cleaning & care instruction
- No release for glue-down
- Technical subjects can be changed by Witex