

piazza with Sound-Protect Eco Plus acoustic system

Description		Direct Pressure Laminate according to EN 13329 for glueless installation	
Fields of use		Laminate piazza is suitable for heavy domestic and heavy commercial use (EN 13329 - 33) "Allgemeine bauaufsichtliche Zulassung": Z-156.606-410	
Technical details		Design	
Dimensions (Decor)	1280 x 192 mm		1 Overlay Especially resistant melamine resin overlay Surface (depend on decor) - fine wooden pore with increased gloss level - matt surface - rough sawn - silk matt
Thickness of element	10 mm		2 Decor paper Decorative film
Package	Pack: 7 elements / 1,72 m ² / 16,77 kg Pallet: 52 packs / 89,44 m ² / 887 kg		3 Underlay Additional strong film
Quality Guarantee*	lifetime		4 Coreboard Aqua-Protect®, FSC certified
Domestic area	10 Jahre		5 Edge sealing Protection against moisture
Commercial area			6 Laminated underlay Sound-Protect Eco Plus acoustic system
			7 Click system (glueless) LocTec click joint
Classification			
		Test Method Standard	Marking acc. Standard
	Level of use 23 Heavy domestic use	EN 13329	Corridors, living rooms, kitchens, home offices
	Level of use 33 Heavy commercial use	EN 13329	Large offices, public buildings, department stores
	LocTec click system	-	Optimum fit with longer durability
	Aqua-Protect® coreboard	-	Especially protected coreboard against moisture
	Suitable for cleaning with Kärcher Steam-Cleaner DE 4002 and Kärcher Floor scrubber BR 400	-	-
	Abrasion resistance	EN 13329, annex E	AC 5
	Impact resistance	EN 13329, annex F	IC 3
	Reaction to fire	DIN 4102 T1 EN 13501-1	B1 C _{fl} s1
	Dynamic coefficient of friction	EN 13893 EN 14041	μ ≥ 0,3 DS
	Anti-Static characteristics	Test of Witex according to DIN EN 1815	Witex laboratory test is fulfilled
	Resistance to staining	EN 438-2	Materials of group 1 + 2: ≥ grade 5 Materials of group 3: ≥ grade 4
	Resistance to cigarette burns	EN 438-2	Slight change of the surface ≥ grade 4
	Impact sound reduction 6	DIN EN ISO 140-8	~ 21 dB
	Light fastness	EN ISO 105 - B02 EN 20105 - A02	Blue wool scale: ≥ 6 Grey scale: ≥ 4
	Static indentation	EN 433	No visible change, i.e. ≤ 0,01 mm indentation using a straight steel cylinder, Ø = 11,30 mm.
	Effect of a furniture leg	EN 424	No visible damage, when tested with foot type 0
	Effect of a castor chair	EN 425	No change in appearance or damage, as defined in EN 425. Single-wheel castors, as defined in EN 12529:1998, 5.4.4.2 (Type W) shall be used.
	Thermal resistance Underfloor heating - suitable in connection with underlay material and PE-foil as moisture barrier	DIN EN 12664	< 0,07 (m ² K)/W - floating installation
	Formaldehyde emission	DIN EN 14041	E1
Environment/Disposal		Private disposal: like laminated furniture; possible with normal domestic refuse Commercial disposal:	Refuse-key-no. AVV 170201

* acc. to the Witex guarantee provisions
** acc. to the Witex implementation provisions

Relevant Information:
- Cleaning and care: see separate cleaning & care instruction
- piazza with Sound Protect Eco Plus acoustic system can also be installed completely glued to the subfloor. Please check details with our technical department.
- Technical subjects can be changed by Witex