

trio clic 3-strip flooring

| Description | | | |
|--|---|---|---|
| Pre-finished parquet produced under precondition EN 13489 - glueless installation with LocTec Wood | | | |
| Fields of use | | | |
| Pre-finished parquet trio clic is suitable for all domestic area | | | |
| Technical details | | Design | |
| Dimensions (Decor) | 2280 x 204 mm | | 1 Wood layer Real wood (approx. 3,4 mm) Wood specifications/grades <i>classic:</i> maple, beech, oak, cherry, iroko, jatoba, walnut, merbau Description classic grade - relatively high evenness of the wood structure - low knot or brown heartwood or splint content - natural colour variation in the wood |
| Thickness of element | 14 mm | | |
| Package | Carton: 6 elements / 2,79 m ² / 20 kg Pallet: 45 cartons / 125,60 m ² / 900 kg | | |
| Quality Guarantee** | Domestic area: 25 years | | |
| | | | |
| | | 2 Middle Core High-quality pine rifts (softwood) and plywood support at the narrow side | 3 Countermove Softwood |
| | | 4 Lacquering UV-Scratch-Protect 6 layers lacquered with matt-finish | 5 Locking system (glueless) LocTec Wood |
| Classification | | | |
| | | Test Method Standard | Marking acc. Standard |
| | Length side Uniclic-system Narrow side Snap-System | - | Automatically aligning at the long side of the element. Perfect fit with longer durability of the end joint connection |
| | UV-Scratch-Protect lacquering | - | - |
| | Level of use C Especially heavy use | ÖNORM C 2354 | Restaurants, salesrooms, premises for the public area |
| | Reaction to fire | EN 13501-1 | C _{fl} - s1 (correspond with B1) |
| | Effect of a castor chair | EN 425 | No visible change Chair wheels type W - use a protection mat in the immediate area of the chair wheels - use felt pads under tables and chairs |
| | Thermal resistance Underfloor heating - suitable up to max. 26 °C surface temperature in connection with PE-foil for moisture barrier | EN 12664 | 0,10 m ² k/W - floating installation (in test) |
| | Formaldehyde emission | EN 14041 | E1 |
| | PEFC - Pan European Forest Certification certified minimum 70 % of the used wood | EN 45011 | Certified from HolzCert Austria |
| | Environment/Disposal like laminated furniture / possible with normal domestic refuse / at commercial heating disposal plant | - | - |

Relevant information:

- Cleaning and care: see separate cleaning & care instruction.
- trio clic can also be installed completely glued to the subfloor. Please check details with our technical department.
- Technical subjects can be changed by Witex.

*) acc. to Witex quality guarantee description